



GENERAL NOTES:

- THIS DIAGRAM DEPICTS THE RELATION OF LINK FUNCTION BLOCK DATA VARIABLES AND OPERATIONS. NAMED VARIABLES MAY POSSESS ONE OR MORE OF THE FOLLOWING ATTRIBUTES AS NOTED:
 PRESET (P) - THE VARIABLE MAY BE PRESET DURING CONFIGURATION.
 SET (S) - THE VARIABLE MAY BE CONNECTED AS AN INPUT AND MAY BE MODIFIED BY SAM IN SPECIAL MODE OR IF A TEST POINT WAS ASSIGNED.
 GET (G) - THE VARIABLE MAY BE ASSIGNED A TEST POINT DURING CONFIGURATION. THE VARIABLE MAY BE EXAMINED BY SAM IN SPECIAL MODE OR IF A TEST POINT WAS ASSIGNED.
 CLOCKED (C) - THE VARIABLE IS DETERMINED AT A SPECIFIED CLOCK RATE.
 TRIGGERED (T OR Trn) - THE VARIABLE IS DETERMINED UPON ANY PRECEDING VARIABLE EVENT OR UPON A SPECIFIC INPUT VARIABLE EVENT IDENTIFIED BY NUMBER.

DWN	H. PRUNER	12 FEB 92	---	SPEED CONTROL	SIZE B	DWG. NO.	RF354337B
CHK	C. PARKER	12 FEB 92	---	CUSTOM/SPEED CONTROL	ISSUE	A1B	
APP			---	LINK FUNCTION BLOCK DATA FLOW DIAGRAM	SCALE		
			---			SHEET	1 OF 1