

Customer:  
Ingeteam

<p><b>INGETEA</b></p> <p>Poland</p> <p>GENERATOR TYPE 6SBV1 450M2-4</p> <p><b>LIST OF BUILT-IN EQUIPMENT</b></p>
--

Contract No.: 601436	Factory No.: 25398, 25399, 25400 25404, 25405, 25406	Part No.: M41296
Issued by: Tech. Department	Prepared by: A. Raduka <i>Raduka</i>	Controlled by: B. Tomičić <i>Tomicić</i>
		Approved by: M. Brčić <i>Brčić</i>

Nr.	LOCATION	DEVICE	TYPE/INPUT/OUTPUT	ALARM/TRIP	LABEL	PRODUCER
1.	STATOR HOUSING	HEATER	300 W, 230 V, 50 Hz	-	H1	ERIK
2.		HEATER			H2	
3.		PT100 THERMOMETER	NWT-ST-B3	Alarm: 70° C	PTH1	ELEKTRON - ERMA
4.		PT100 THERMOMETER	Max. operating current: 10 mA	Trip: 100° C	PTH2	
5.		WATER LEAKAGE DETECTOR	ALBA-MU-M55-SVK44A	-	WLD1	KUBLER
6.	STATOR WINDING (SLOT SPACER)	PT100 THERMOMETER	NWT-ST-B3 Max. operating current: 10 mA	Alarm: 155° C Trip: 180° C	PTU1	EPHY-MESS
7.		PT100 THERMOMETER			PTU2	
8.		PT100 THERMOMETER			PTV1	
9.		PT100 THERMOMETER			PTV2	
10.		PT100 THERMOMETER			PTW1	
11.	PT100 THERMOMETER	PTW2				
12.	DE BEARING	PT100 THERMOMETER	Max. operating current: 10 mA	Alarm: 80° C Trip: 100° C	PTDE1	ELEKTRON - ERMA
13.		PT100 THERMOMETER			PTDE2	
14.		Connection nipple	TPEV Operating temperature: -60 to 110 °C	-	CNDE1	SPM
15.	NDE BEARING	PT100 THERMOMETER	Max. operating current: 10 mA	Alarm: 80° C Trip: 100° C	PTNDE1	ELEKTRON - ERMA
16.		PT100 THERMOMETER			PTNDE2	
17.		Connection nipple	TPEV Operating temperature: -60 to 110 °C	-	CNNDE1	SPM
18.	DE SIDE	CARBON BRUSH	-	-	CB1	SCHUNK
19.	MAIN TERMINAL BOX	VOLTAGE TRANSFORMER	VTM 690 / 110; 20 VA; cl. 0,5	-	VT1	ELEKTRO-SKLOP
20.		VOLTAGE TRANSFORMER			VT2	



Nr.	LOCATION	DEVICE	TYPE/INPUT/OUTPUT	ALARM/TRIP	LABEL	PRODUCER
21.	NEUTRAL TERMINAL BOX	CURRENT TRANSFORMER	CTB3-1500 1500/1/1 A; 15 VA; 5P10, cl. 0,5	-	CTU2	ELEKTRO- SKLOP
22.		CURRENT TRANSFORMER			CTV2	
23.		CURRENT TRANSFORMER	CTW2			
24.		CURRENT TRANSFORMER	CTB3-1500 1500/1 A; 15 VA; cl. 0,5		CTAVR	ELEKTRO- SKLOP
25.	AUXILIARY TERMINAL BOX	3-POLE CIRCUIT BREAKER WITH 2 AUXILIARY CONTACTS	4A S203-K4	-	Q1	KT ABB
26.		3-POLE CIRCUIT BREAKER WITH 2 AUXILIARY CONTACTS	20A S203-K		Q2	